



# F&J SPECIALTY PRODUCTS, INC.

*The Nucleus of Quality Air Monitoring Programs*

## EMERGENCY RESPONSE AIR SAMPLING SYSTEM DIGITAL FLOW METER TECHNOLOGY F&J MODEL DFRV-ABM50-40L-30Li

### NOTABLE FEATURES:

- State-of-the-Art Electronics
- Operating Modes
  - Line Power (100VAC – 250VAC)
  - On-board 30 Ah LiFe(PO<sub>4</sub>) rechargeable battery
- Lightweight — 22 lbs. (9.98 kg)
- Maximum Flow 40L SLPM Maximum with 47 mm glass fiber media (98% DOP efficiency) FP47M
- Bright LED Display
- Automatic Flow Control Feature
- Flowrate and Volume totalizations displayed are corrected to a factory settable Reference Temperature and Pressure (4 options available)
- Auto shut-off on time or volume
- Battery Life Indicator
- Brushless motor (12 VDC)
- Data Download via Bluetooth with Optional Bluetooth Dongle for PC Device



**Shown with optional  
filter holder FJ-34**

### NOTABLE FEATURES:

F&J Model DFRV-ABM50-40L-30Li is a military grade lightweight, small footprint, AC/DC voltage powered air sampling system operable from (1) line power, or (2) an on-board 30 Ah LiFe(PO<sub>4</sub>) battery.

The DFRV-ABM50-40L-30Li is well suited for emergency response air sampling activities and where users do not know whether line power will be available. Typical operating time from on-board battery is approximately 10—12 hours utilizing FP47M glass fiber filter paper.

The automatic flow control feature with the F&J Digital Flowmeter technology provides maximum flexibility for emergency response sampling responsibilities. The set flowrate is maintained automatically in case of dust loading and does not require operator attention. The air sampler is contained in a rugged, metal, small dimensioned enclosure which is water tight. The unit can be carried very easily by its metal handle.

Typical flow range is 5 - 40 SLPM (0.18 – 1.41 SCFM). This flow rate varies by the filter media utilized. If pressure drop across the filter media is not significant lower flow will not be achievable without bypass valve option.

The air sampler is also equipped with internal data storage that allows the user to download the sampling data as a .csv file for easy data analysis.

REV: 18 November 2024

# DFRV-ABM50-40L-30Li AC/DC Powered Air Sampler Specifications

**Pump Type:** Mini rotary vacuum pump

**Motor:** Brushless motor 12 VDC

**Maximum Flowrate:** 40 LPM typical  
with 47 mm glass fiber media (98% DOP efficiency) FP47M

**Power Source:**  
Line Power; 100VAC to 240VAC  
On-board LiFe(PO<sub>4</sub>) battery (20 Ah/12.8 VDC)/30Ah

**Current Draw:** 4.0 A maximum

**Operating Time on Battery:** ~10-12 hours with FP47M

**Filter Holder Fitting:** 3/8 FNPT quick disconnect

**Enclosure:** Steel

**Handle:** Durable metal

**Weight:** 22 lbs. (9.98 kg)

**Dimensions:** 13.8"L × 9.5"W × 9"H  
(35.0 × 24.2 × 22.8 cm)

**Average dBA:** 67.5

**Operating Temperature Range:**  
14°F to 122°F (-10°C to 50°C)

**Display:** Bright LED (6 character, 1,2 cm H)

**Elapsed Time:** DD:HH:MM up to 168 hours

**Flow Control:**  
Adjustable from keypad between 5-40 LPM

**Flow Accuracy:** ±4.0% of Full Scale

**Factory Settable Reference T and P**

Classical STP	0°C, 1 ATM
Normal T and P	20°C, 1 ATM
Modified Normal T and P	70°F, 1 ATM
Standard Ambient T and P	25°C, 1 ATM

## OPTIONS:

- Bypass Needle Valve
- Bluetooth Dongle for PC Device (P/N: BTDG)

## Optional

**Standard Combination Filter Holders Available:**

FILTER HOLDER MODEL	CHARCOAL CARTRIDGE DIMENSIONS	PARTICULATE PAPER DIAM- ETER
FJ-19	F&J Model C	2" or 50 mm
FJ-27	F&J Model B	2" or 50 mm
FJ-34	F&J Model C	47 mm
FJ-39	F&J Model B	47 mm
FJ-52	F&J Model M	2" or 50 mm
FJ-54	F&J Model M	47 mm

**Filter holders for 102 mm and 110 mm are available**

**Available Engineering Units for Flow and Volume:**

SLPM / SL  
SCFM / SCF  
SCMH / SCM

## Digital Flowmeter Keypad/Display

